

Date of issue: 31.08.2022

Date of update: —

Version: 1.0/EN

[Prepared in accordance with Regulation EC 1907/2006 (REACH), as amended]

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name: ECOLO - WINTER ICE
UFI: 21X2-F0C6-H00Q-0WDT

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses: air freshener.
Uses advised against: not determined.

1.3. Details of the supplier of the safety data sheet

Manufacturer: Dr. MARCUS International Sp. z o.o. Sp. k.

Address: Aleja Wojska Polskiego 2C, 62-800 Kalisz, PL

Telephone/fax: + 48 62 760 07 00 / +48 62 760 07 59

E-mail address for a competent person responsible for SDS: drmarcus@dr-marcus.com

1.4. Emergency telephone number

112 (general emergency telephone number)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Flam. Liq. 3 H226, Skin Irrit. 2 H315, Skin Sens. 1 H317, STOT SE 3 H336, Aquatic Chronic 2 H411

Flammable liquid and vapour. Causes skin irritation. May cause an allergic skin reaction. May cause drowsiness or dizziness. Toxic to aquatic life with long lasting effects.

2.2. Label elements

Hazard pictograms and signal words







Warning

Hazardous components placed on the label

Contains: 1-methoxy-2-propanol; linalool; limonene; geranyl acetate; 1-(1,2,3,4,5,6,7,8-octahydro-2,3,8,8-

 $tetramethyl-2-naphthyl) ethan-1-one; \ 3-p-cumenyl-2-methylpropional dehyde; \ citronellol; \ citral; \ 6.8-dimethylnon-7-enal; \ pin-2(10)-ene; \ 2.4-dimethylcyclohex-3-ene-1-carbaldehyde; \ 1-(2.6.6-trimethyl-2-meth$

3-cyclohexen-1-yl)-2-buten-1-one; isoeugenol.

Hazard statements

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P273 Avoid release to the environment.

P302+P352 IF ON SKIN: Wash with plenty of water and soap.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.





[Prepared in accordance with Regulation EC 1907/2006 (REACH), as amended]

P501

Dispose of contents/container to properly labelled waste containers according to national law.

Additional information

None.

2.3. Other hazards

Product does not contain components, which meet criteria for PBT or vPvB in accordance with Annex XIII of REACH Regulation.

The product does not contain substances included in the list established in accordance with Article 59(1) for having endocrine disrupting properties, or substances identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 (3) or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 % by weight.

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable.

3.2. Mixtures

| CAS number: 107-98-2 EC number: 203-539-1 Index number: 603-064-00-3 Registration number: 01-2119457435-35-XXXX | 1-methoxy-2-propanol ¹⁾ Flam. Liq. 3 H226, STOT SE 3 H336 | C < 40 % |
|---|---|-----------|
| CAS number: 34590-94-8 EC number: 252-104-2 Index number: — Registration number: 01-2119450011-60-XXXX | (2-methoxymethylethoxy)propanol ¹⁾ The substance is not classified as hazardous. | C < 25 % |
| CAS number: 78-70-6 EC number: 201-134-4 Index number: 603-235-00-2 Registration number: 01-2119474016-42-XXXX | linalool Skin Irrit. 2 H315, Skin Sens. 1B H317, Eye Irrit. 2 H319 | C < 5 % |
| CAS number: 58430-94-7 EC number: 261-245-9 Index number: — Registration number: 01-2119972325-34-XXXX | 3,5,5-trimethylhexyl acetate Skin Irrit. 2 H315, Aquatic Chronic 2 H411 | C < 5 % |
| CAS number: 138-86-3 EC number: 205-341-0 Index number: 601-029-00-7 Registration number: — | limonene Flam. Liq. 3 H226, Asp. Tox. 1 H304, Skin Irrit. 2 H315, Skin Sens. 1B H317, Aquatic Acute 1 H400 (M=1), Aquatic Chronic 1 H410 (M=1) Note C | C < 2,2 % |
| CAS number: 63500-71-0 EC number: 405-040-6 Index number: 603-101-00-3 Registration number: — | tetrahydro-2-isobutyl-4-methylpyran-4-ol, mixed isomers (cis and trans) Eye Irrit. 2 H319 | C ≤ 2 % |
| CAS number: 14901-07-6 EC number: 238-969-9 Index number: — Registration number: — | beta ionone Aquatic Chronic 2 H411 | C < 2 % |

Dr. MARCUS

Safety Data Sheet

[Prepared in accordance with Regulation EC 1907/2006 (REACH), as amended]

| CAS number: 105-87-3 EC number: 203-341-5 Index number: — Registration number: 01-2119973480-35-XXXX | geranyl acetate Skin Irrit. 2 H315, Skin Sens. 1 H317, Aquatic Chronic 3 H412 | C < 0,5 % |
|--|---|------------|
| CAS number: 54464-57-2 EC number: 259-174-3 Index number: — Registration number: — | 1-(1,2,3,4,5,6,7,8-octahydro-2,3,8,8-tetramethyl-2-naphthyl)ethan-1-one Skin Irrit. 2 H315, Skin Sens. 1B H317, Aquatic Chronic 1 H410 (M=1) | C < 0,5 % |
| CAS number: 103-95-7 EC number: 203-161-7 Index number: — Registration number: 01-2119970582-32-XXXX | 3-p-cumenyl-2-methylpropionaldehyde Skin Irrit. 2 H315, Skin Sens. 1B H317, Aquatic Chronic 3 H412 | C < 0,35 % |
| CAS number: 106-22-9 EC number: 203-375-0 Index number: — Registration number: 01-2119453995-23-XXXX | citronellol Skin Irrit. 2 H315, Skin Sens. 1 H317, Eye Irrit. 2 H319 | C < 0,35 % |
| CAS number: 5392-40-5 EC number: 226-394-6 Index number: 605-019-00-3 Registration number: 01-2119462829-23-XXXX | citral Skin Irrit. 2 H315, Skin Sens. 1 H317, Eye Irrit. 2 H319 | C < 0,25 % |
| CAS number: 899810-84-5 EC number: 687-633-1 Index number: — Registration number: — | 6,8-dimethylnon-7-enal Skin Sens. 1 H317, Aquatic Acute 1 H400 (M=1) | C < 0,25 % |
| CAS number: 127-91-3 EC number: 204-872-5 Index number: — Registration number: 01-2119519230-54-XXXX | pin-2(10)-ene Flam. Liq. 3 H226, Asp. Tox. 1 H304, Skin Irrit. 2 H315, Skin Sens. 1B H317, Aquatic Acute 1 H400 (M=1), Aquatic Chronic 1 H410 (M=1) | C < 0,25 % |
| CAS number: 68039-49-6 EC number: 268-264-1 Index number: — Registration number: — | 2,4-dimethylcyclohex-3-ene-1-carbaldehyde Skin Irrit. 2 H315, Skin Sens. 1B H317, Eye Irrit. 2 H319, Aquatic Chronic 2 H411 | C < 0,25 % |
| CAS number: 99-85-4 EC number: 202-794-6 Index number: — Registration number: 01-2120780478-40-XXXX | p-mentha-1,4-diene Flam. Liq. 3 H226, Asp. Tox. 1 H304, Repr. 2 H361, Aquatic Chronic 2 H411 | C < 0,25 % |
| CAS number: 57378-68-4 EC number: 260-709-8 Index number: — Registration number: — | 1-(2,6,6-trimethyl-3-cyclohexen-1-yl)-2-buten-1-one Acute Tox. 4 H302, Skin Irrit. 2 H315, Skin Sens. 1A H317, Aquatic Acute 1 H400 (M=1), Aquatic Chronic 1 H410 (M=1) | C < 0,05 % |



Date of issue: 31.08.2022

Date of update: —

Version: 1.0/EN

[Prepared in accordance with Regulation EC 1907/2006 (REACH), as amended]

| CAS number: 97-54-1 | isoeugenol | |
|----------------------------|--|-------------|
| EC number: 202-590-7 | Acute Tox. 4 H302, Acute Tox. 4 H312, Skin Irrit. 2 H315, Skin | |
| Index number: 604-094-00-X | Sens. 1A H317, Eye Irrit. 2 H319, Acute Tox. 4 H332, STOT SE | C + 0.03E W |
| Registration number: — | 3 H335 | C < 0,025 % |
| | Specific concentration limits: | |
| | Skin Sens. 1A H317: C ≥ 0,01% | |

¹⁾ Substance with occupational exposure limits established on the European Union level.

Full text of each H phrase is given in section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

Contact with skin

Consult a doctor if disturbing symptoms appear. Take off contaminated clothing. Wash the exposed parts of the skin thoroughly with water and soap.

Contact with eyes

Consult a ophthalmologist if disturbing symptoms appear. Protect non-irritated eye, remove contact lenses. Rinse contaminated eyes thoroughly with water for 10 - 15 minutes. Avoid powerful water stream – risk of cornea damage.

Ingestion

Consult a doctor, show the packaging or label. Do not induce vomiting. Rinse mouth with water. Never give anything by mouth to an unconscious person.

After inhalation

Remove the victim to fresh air, keep warm and at rest. Consult a doctor if disturbing symptoms appear.

4.2. Most important symptoms and effects, both acute and delayed

Contact with skin

The product may cause redness, burning sensation, irritation, allergic reaction.

Contact with eyes

The product may cause burning sensation, tearing.

Ingestion

May cause nausea, abdominal pains.

After inhalation

High concentration of vapours and mists may cause headaches, dizziness.

Effects of exposure

Not known.

4.3. Indication of any immediate medical attention and special treatment needed

Physician makes a decision regarding further medical treatment after thoroughly examination of the injured. Symptomatic treatment.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media: adapt the extinguishing media to surrounding materials.

Unsuitable extinguishing media: water jet – risk of the propagation of the flame.

5.2. Special hazards arising from the substance or mixture

During the fire may produce harmful gases containing e.g. carbon monoxides, other hazardous unidentified products of thermal decomposition. Do not inhale combustion products, they can be dangerous for human health.



Date of issue: 31.08.2022

Date of update: —

Version: 1.0/EN

[Prepared in accordance with Regulation EC 1907/2006 (REACH), as amended]

5.3. Advice for firefighters

Flammable liquid and vapour. Vapours are heavier than air, they accumulate in the lower parts of the premises and pose a risk of explosion. Personal protection typical in case of fire. Do not stay in the fire zone without self-contained breathing apparatus and protective clothing resistant to chemicals. Cool down the containers that are endangered by fire with a water spray from a safe distance. Collect used extinguishing media.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Limit the access for the outsiders into the breakdown area, until the suitable cleaning operations are completed. Ensure that only the trained personnel removes the effects of the accident. In case of large spills, isolate the exposed area. Use personal protective equipment. Eliminate all sources of ignition - do not use an open flame, do not smoke, do not use sparking tools, etc.

6.2. Environmental precautions

Do not allow the product to get into the sewage system, surface waters and soil. In case of release of large amounts of the product, it is necessary to take appropriate steps to prevent it from spreading into the environment. Notify relevant emergency services.

6.3. Methods and material for containment and cleaning up

Small leakage: collect the spilled product with incombustible absorbing materials (e.g. sand, earth, universal binding agents, silica etc.) and place it in waste containers. Treat the collected material as waste. Clean and ventilate the contaminated area. Large leakage: isolate places where liquid accumulates; pump the collected liquid out.

6.4. Reference to other sections

Appropriate conduct with waste product – see section 13. Personal protective equipment – see section 8.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Handle in accordance with good occupational hygiene and safety practices. Avoid eyes and skin contamination. Before break and after work wash hands carefully. Keep the unused containers tightly closed. Provide general and / or local ventilation in the workplace in order to maintain the concentration of the harmful agent in the air below the established limit values. Avoid vapor formation. Use personal protective equipment. Eliminate sources of ignition - do not use an open flame, do not smoke, do not use sparking tools and clothes made of fabrics susceptible to static electricity.

7.2. Conditions for safe storage, including any incompatibilities

Store in properly labeled, sealed packages in a dry, cool and well-ventilated place. Keep away from incompatible materials (see subsection 10.5). Keep away from, foodstuffs and animal feed. Keep away from sources of fire. Smoking, using open fire and sparking tools is prohibited in the warehouse.

7.3. Specific end use(s)

No information about other uses than those mentioned in subsection 1.2.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational Exposure Limit Values

Legal Basis: Commission Directive 2000/39/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU, 2019/1831/EU.

| 9 | | | |
|---------------------------------|------------|-----------------------|----------|
| Specification | TWA 8 hour | STEL 15 min | Notation |
| 1-methoxy-2-propanol | 375 mg/m³ | 568 mg/m ³ | skin |
| (2-methoxymethylethoxy)propanol | 308 mg/m³ | _ | skin |

Skin - means that skin absorption of a substance may be just as important as inhalation exposure.

 $Legal\ Basis:\ EH40/2005\ Workplace\ exposure\ limits.\ Fourth\ Edition\ 2020.$





[Prepared in accordance with Regulation EC 1907/2006 (REACH), as amended]

Recommended control procedures

Procedures for monitoring concentrations of hazardous components in the air and procedures for monitoring air purity in the workplace should be applied - if available and justified at a given position - in accordance with the relevant national or European Standards, taking into account the conditions at the site of exposure and the appropriate measurement methods adapted to the working conditions. The mode, type and frequency of tests and measurements should meet the requirements of the appropriate laws.


DNEL and PNEC

| 1-methoxy-2-propanol [CAS 107-98-2] | | | | |
|-------------------------------------|---------------------|-----------------|------------------|--|
| Francisco no reto | | DNEL | | |
| Exposure route | Exposure scheme | worker | consumer | |
| inhalation | short-term local | _ | 553,5 mg/m³ | |
| inhalation | long-term systemic | 43,9 mg/m³ | 369 mg/m³ | |
| skin | long-term systemic | 78 mg/kg bw/day | 183 mg/kg bw/day | |
| oral | long-term systemic | _ | 33 mg/kg bw/day | |
| inhalation | short-term systemic | _ | 553,5 mg/m³ | |

| 1-methoxy-2-propanol [CAS 107-98-2] | | |
|-------------------------------------|-----------------------|--|
| PNEC | Value | |
| marine water | 1 mg/l | |
| freshwater | 10 mg/l | |
| soil | 4,59 mg/kg dry weight | |
| freshwater sediment | 52,3 mg/kg dry weight | |
| marine water sediment | 5,2 mg/kg dry weight | |
| sewage treatment plant | 100 mg/l | |
| freshwater (intermittent release) | 100 mg/l | |

| (2-methoxymethylethoxy)propanol [CAS 34590-94-8] | | | | |
|--|--------------------|------------------|------------------|--|
| DNEL | | | NEL | |
| Exposure route | Exposure scheme | worker | consumer | |
| inhalation | long-term systemic | 37,2 mg/m³ | 308 mg/m³ | |
| skin | long-term systemic | 121 mg/kg bw/day | 283 mg/kg bw/day | |
| oral | long-term systemic | _ | 36 mg/kg bw/day | |

| (2-methoxymethylethoxy)propanol [CAS 34590-94-8] | | |
|--|-----------------------|--|
| PNEC | Value | |
| marine water | 1,9 mg/l | |
| freshwater | 19 mg/l | |
| soil | 2,74 mg/kg dry weight | |
| freshwater sediment | 70,2 mg/kg dry weight | |
| marine water sediment | 7,02 mg/kg dry weight | |
| sewage treatment plant | 4168 mg/l | |
| freshwater (intermittent release) | 190 mg/l | |





[Prepared in accordance with Regulation EC 1907/2006 (REACH), as amended]

| linalool [CAS 78-70-6] | | | | |
|------------------------|--------------------|----------------------|------------------------|--|
| F | | DNEL | | |
| Exposure route | Exposure scheme | worker | consumer | |
| inhalation | long-term systemic | 24,58 mg/m³ | 4,33 mg/m³ | |
| oral | long-term systemic | _ | 2,49 mg/kg bw/day | |
| skin | long-term systemic | 3,5 mg/kg bw/day | 1,25 mg/kg bw/day | |
| skin | long-term local | 3 mg/cm ² | 1,5 mg/cm ² | |
| skin | short-term local | 3 mg/cm ² | 1,5 mg/cm ² | |

| linalool [CAS 78-70-6] | | |
|-----------------------------------|------------------------|--|
| PNEC | Value | |
| marine water | 0,02 mg/l | |
| freshwater | 0,2 mg/l | |
| soil | 0,327 mg/kg dry weight | |
| freshwater sediment | 2,22 mg/kg dry weight | |
| marine water sediment | 0,222 mg/kg dry weight | |
| sewage treatment plant | 10 mg/l | |
| secondary poisoning | 7,8 mg/kg food | |
| freshwater (intermittent release) | 2 mg/l | |

8.2. Exposure controls

Industrial hygiene

Use the product in accordance with good occupational hygiene and safety practices. Do not eat, drink and smoke during the work. Before break and after work wash hands carefully. Ensure adequate general and/or local ventilation at the workplace. If during work processes there is a risk of clothing fire on the employee - no more than 20 m in a horizontal line from the stations where these processes are performed, emergency showers (safety showers) for washing the whole body and separate showers (showers) for eye washing should be installed.

Individual protection measures

The necessity to use and the selection of appropriate personal protective equipment should take into account the type of risk posed by the product, working conditions and the way of handling the product. The personal protective equipment used must meet the requirements of Regulation (EU) 2016/425 and the relevant standards. The employer is obliged to provide protection measures appropriate to the activities performed and meeting all quality requirements, including their maintenance and cleaning. Any contaminated or damaged PPE must be replaced immediately.

Hand protection

Use protective gloves resistant to chemicals according to EN 374. In case of a long-term, frequent contact with the product, in the event of a failure, protective gloves with the effectiveness level 2 or higher are recommended. Recommended material for gloves: nitrile rubber, neoprene.

The glove material has to be impermeable and resistant to the product. The choice of material for protective gloves should be made taking into account the breakthrough times, permeation rate and degradation. Moreover, the selection of the appropriate gloves does not only depend on the material, but also on other quality characteristics and varies from manufacturer to manufacturer. The exact breakthrough time has to be obtained from the glove manufacturer and it must be observed.

Body protection

Use skin protection measures adequate to the existing thermal, chemical or mechanical hazards.

Eye protection

If there is a risk of eye contamination, use safety glasses in accordance with the EN 166 standard.



Date of issue: 31.08.2022

Date of update: —

Version: 1.0/EN

[Prepared in accordance with Regulation EC 1907/2006 (REACH), as amended]

Respiratory protection

In cases where the risk assessment indicates that it is necessary, respiratory protective equipment compliant with the EN136 standard (masks) or EN 140 (half masks, quarter masks) should be used.

Thermal hazards

Not applicable.

Environmental exposure controls

Prevent direct release to drains/ surface waters. Do not contaminate surface waters and drainage ditches with chemicals or used containers. Released product or uncontrolled spills to surface waters should be reported to appropriate authorities in accordance with local and national legislations. Dispose as chemical waste, in accordance with local and national legislation.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: liquid
Colour: light blue

Odour: characteristic, pleasant

Melting point/freezing point: not determined

Boiling point or initial boiling point and boiling

range: not determined
Flammability: not applicable

Lower and upper explosion limit: 1,1 % / 14% obj. (CAS 34590-94-8); 1,48 % / 13,7 % obj. (CAS 107-98-

2)

Flash point: 44,5 °C

Auto-ignition temperature: not determined

Decomposition temperature: not determined

pH: not determined

Kinematic viscosity: not determined

Solubility: not soluble in water; creates a suspension in water

Partition coefficient n-octanol/water (log value): not applicable

Vapour pressure: not determined

Density and/or relative density: not determined

Relative vapour density: not determined

Particle characteristics: not applicable

9.2. Other information

No additional tests.

SECTION 10: Stability and reactivity

10.1. Reactivity

Product is reactive. It does not go under hazardous polimeryzation. Product's vapours may form explosive mixtures with air. See also subsection 10.3-10.5.

10.2. Chemical stability

The product is stable under normal conditions of use and storage.

10.3. Possibility of hazardous reactions

Hazardous reactions are not known.

10.4. Conditions to avoid

Avoid heat sources, open flames, sparking tools and direct sunlight.



Date of issue: 31.08.2022

Date of update: —

Version: 1.0/EN

[Prepared in accordance with Regulation EC 1907/2006 (REACH), as amended]

10.5. Incompatible materials

Avoid contact with following materials: strong oxidants.

10.6. Hazardous decomposition products

Not known.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

| Acute toxicity | | | |
|---|--------------|--|--|
| 1-methoxy-2-propanol [CAS 107-98-2] | | | |
| LD50 (oral, rat) | 3739 mg/kg | | |
| LD50 (skin, rat) | > 2000 mg/kg | | |
| (2-methoxymethylethoxy)propanol [CAS 34590-94 | 8j | | |
| LD50 (oral, rat) | > 5000 mg/kg | | |
| LDso (skin, rabbit) | 9510 mg/kg | | |
| linalool [CAS 78-70-6] | | | |
| LC50 (inhalation, mouse) | > 20 mg/1h | | |
| LD50 (oral, rat) | 2790 mg/kg | | |
| LD50 (skin, rat) | 5610 mg/kg | | |
| 3,5,5-trimethylhexyl acetate [CAS 58430-94-7] | | | |
| LD ₅₀ (oral, rat) | 4250 mg/kg | | |
| LD50 (skin, rabbit) | > 5000 mg/kg | | |

Mixture

Based on available data, the classification criteria are not met.

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/irritation

Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation

May cause an allergic skin reaction.

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Carcinogenicity

Based on available data, the classification criteria are not met.

Reproductive toxicity

Based on available data, the classification criteria are not met.

STOT-single exposure

Product vapours may cause headaches, dizziness and drowsiness.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.





[Prepared in accordance with Regulation EC 1907/2006 (REACH), as amended]

Information on likely routes of exposure

Exposure route: eye exposure, skin exposure, inhalation, ingestion. For more information on the impact of each possible route of exposure, see subsection 4.2.

Symptoms related to the physical, chemical and toxicological characteristics

See subsection 4.2 of the SDS.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

See subsection 4.2 of the SDS.

11.2. Information on other hazards

Endocrine disrupting properties

The product does not contain substances included in the list established in accordance with Article 59(1) for having endocrine disrupting properties, or substances identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 (3) or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 % by weight.

Other information

No data on other hazards.

SECTION 12: Ecological information

Toxic to aquatic life with long lasting effects.

12.1. Toxicity

| 1-methoxy-2-propanol [CAS 107-98-2] | | | |
|-------------------------------------|---|---|--|
| LC50 (fish) | > 6812 mg/l / 96 h / Leuciscus idus | method: DIN 38412 | |
| (2-methoxymethylethoxy)propanol | [CAS 34590-94-8] | | |
| LC50 (fish) | > 1000 mg/l / 96 h / Poecilia reticulata | method: OECD 203 / EU C.1 | |
| NOEC (invertebrates) | ≥ 0,5 mg/l / 22 days / Daphnia magna | method: OECD 211 | |
| NOEC (algae) | 969 mg/l / 72 h / Pseudokirchneriella subcapitata | method: OECD 201 / EU C.3 / EPA OTS 797.1050 | |
| EC ₁₀ (microorganisms) | 4168 mg/l / 18 h / Pseudomonas putida | method: — | |
| linalool [CAS 78-70-6] | | | |
| LC50 (fish) | 27,8 mg/l / 96 h / Oncorhynchus mykiss | method: OECD 203 | |
| EC ₅₀ (invertebrates) | 59 mg/l / 48 h / Daphnia magna | method: OECD 202 | |
| EC50 (microorganisms) | > 100 mg/l / 3 h / — | method: OECD 209 | |
| 3,5,5-trimethylhexyl acetate [CAS ! | 58430-94-7] | | |
| LCso (fish) | 7,7 mg/l / 96 h / Pimephales promelas | method: OECD 203 / EPA OPPTS 850.1075 | |
| EC50 (invertebrates) | > 5,8 mg/l / 48 h / Daphnia magna | method: OECD 202 / EPA OPPTS 850.1010 | |
| EC50 (algae) | 1,3 mg/l / 72 h / Pseudokirchneriella subcapitata | method: OECD 201 / EU Metoda C.3 / EPA OPPTS 850.5400 | |
| NOEC (microorganisms) | 100 mg/l / 32 days / — | method: — | |
| Mixture | | | |





[Prepared in accordance with Regulation EC 1907/2006 (REACH), as amended]

12.2. Persistence and degradability

| 1-methoxy-2-propanol CAS 107-98-2 | Easily biodegradable | 96%/28 days | method: OECD 301 E |
|---|----------------------|---------------|--------------------|
| (2-methoxymethylethoxy)propanol CAS 34590-94-8 | Easily biodegradable | 76%/28 days | method: OECD 301 F |
| linalool CAS 78-70-6 | Easily biodegradable | 64,2%/28 days | method: OECD 301 D |
| 3,5,5-trimethylhexyl acetate CAS 58430-94-7 | Easily biodegradable | 80%/28 days | method: OECD 301 F |

12.3. Bioaccumulative potential

| 1-methoxy-2-propanol | log Po/w = < 1 | method: OECD 117 |
|---------------------------------|---------------------------|------------------|
| CAS 107-98-2 | BCF = | method: — |
| (2-methoxymethylethoxy)propanol | log Po/w = 0,004 | method: OECD 107 |
| CAS 34590-94-8 | BCF = | method: — |
| | | |
| linalool | log Po/w = 2,9 | method: — |
| linalool CAS 78-70-6 | log Po/w = 2,9 BCF = — | method: — |
| | 3 ' ' | |

12.4. Mobility in soil

Mobility of components of the mixture in soil depends on the hydrophilic and hydrophobic properties and biotic and abiotic conditions of soil, including its structure, climatic conditions, seasons and soil organisms.

12.5. Results of PBT and vPvB assessment

Product does not contain components, which meet criteria for PBT or vPvB in accordance with Annex XIII of REACH Regulation.

12.6. Endocrine disrupting properties

The product does not contain substances included in the list established in accordance with Article 59(1) for having endocrine disrupting properties, or substances identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 (3) or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 % by weight.

12.7. Other adverse effects

The mixture is not classified as hazardous to the ozone layer. Consider other harmful effects of individual components of the mixture on the environment (eg, global warming potential).

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Recommendations for the product

The waste product should be recovered or disposed of in authorized incineration plants or waste disposal / neutralization plants, in accordance with applicable regulations. Do not empty into drains. The waste code should be given in the place of its formation.

Recommendations for used packaging

Reuse / recycle / eliminate empty containers in accordance with the local legislation. Only completely empty containers can be reused.



Date of issue: 31.08.2022

Date of update: —

Version: 1.0/EN

[Prepared in accordance with Regulation EC 1907/2006 (REACH), as amended]

EU legal acts: directives of the European Parliament and of the Council: 2008/98 / EC as amended and 94/62 / EC as amended.

Recommended waste codes

The waste code should be assigned at the place of its formation.

SECTION 14: Transport information

14.1. UN number or ID number

UN 1993

14.2.UN proper shipping name

ADR

FLAMMABLE LIQUID, N.O.S. [1-METHOXY-2-PROPANOL]

IMDG

FLAMMABLE LIQUID, N.O.S. [1-METHOXY-2-PROPANOL]

ICAO/IATA

FLAMMABLE LIQUID, N.O.S.

[1-METHOXY-2-PROPANOL]

14.3. Transport hazard class(es)

3

14.4. Packing group

Ш

14.5. Environmental hazards

ADR yes
IMDG yes
ICAO/IATA yes

14.6. Special precautions for user

Avoid sources of heat and fire. Use personal protective equipment according to section 8 when handling the product.

220 L

14.7. Maritime transport in bulk according to IMO instruments

Not applicable.

Additional data

| ADR | limited quantity LQ | 5 L |
|-----------|--------------------------------|----------|
| | transport category | 3 |
| | tunnel restriction code | D/E |
| IMDG | limited quantity LQ | 5 L |
| | EmS code | F-E, S-E |
| ICAO/IATA | packing instruction (LQ) | Y344 |
| | limited quantity (LQ) | 10 L |
| | packing instruction, passenger | 355 |
| | | |
| | maximum quantity, passenger | 60 L |

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

ADR Agreement concerning the International Carriage of Dangerous Goods by Road.

maximum quantity, cargo



Date of issue: 31.08.2022

Date of update: —

Version: 1.0/EN

[Prepared in accordance with Regulation EC 1907/2006 (REACH), as amended]

2000/39/EC COMMISSION DIRECTIVE of 8 June 2000 establishing a first list of indicative occupational exposure limit values in implementation of Council Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work.

2006/15/EC COMMISSION DIRECTIVE of 7 February 2006 establishing a second list of indicative occupational exposure limit values in implementation of Council Directive 98/24/EC and amending Directives 91/322/EEC and 2000/39/EC.

2009/161/EU COMMISSION DIRECTIVE of 17 December 2009 establishing a third list of indicative occupational exposure limit values in implementation of Council Directive 98/24/EC and amending Commission Directive 2000/39/EC.

2017/164/EU COMMISSION DIRof 31 January 2017 establishing a fourth list of indicative occupational exposure limit values pursuant to Council Directive 98/24/EC, and amending Commission Directives 91/322/EEC, 2000/39/EC and 2009/161/EU.

2019/1831/EU COMMISSION DIRECTIVE of 24 October 2019 establishing a fifth list of indicative occupational exposure limit values pursuant to Council Directive 98/24/EC and amending Commission Directive 2000/39/EC.

2016/425/EU REGULATION OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 9 March 2016 on personal protective equipment and repealing Council Directive 89/686/EEC.

1907/2006/EC REGULATION OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC (as amended).

2020/878/EU COMMISSION REGULATION of 18 June 2020 amending Annex II to Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals.. 1272/2008/EC REGULATION OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 (as amended).

2008/98/EC DIRECTIVE OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 19 November 2008 on waste and repealing certain Directives (as amended).

European Parliament and Council Directive 94/62/EC of 20 December 1994 on packaging and packaging waste as amended

15.2. Chemical safety assessment

A Chemical Safety Assessment is not required for mixtures.

SECTION 16: Other information

| Full text of H phrases mentioned in section 3 | | |
|---|--------|--|
| | H226 | Flammable liquid and vapour. |
| | H302 | Harmful if swallowed. |
| | H304 | May be fatal if swallowed and enters airways. |
| | H312 | Harmful in contact with skin. |
| | H315 | Causes skin irritation. |
| | H317 | May cause an allergic skin reaction. |
| | H319 | Causes serious eye irritation. |
| | H332 | Harmful if inhaled. |
| | H335 | May cause respiratory irritation. |
| | H336 | May cause drowsiness or dizziness. |
| | H361 | Suspected of damaging fertility or the unborn child. |
| | H400 | Very toxic to aquatic life. |
| | H410 | Very toxic to aquatic life with long lasting effects. |
| | H411 | Toxic to aquatic life with long lasting effects. |
| | H412 | Harmful to aquatic life with long lasting effects. |
| | Note C | Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers. |

Clarification of abbreviations and acronyms

ADR Agreement concerning the International Carriage of Dangerous Goods by Road.

DIN German Institute for Standardization



Date of issue: 31.08.2022

Date of update: —

Version: 1.0/EN

[Prepared in accordance with Regulation EC 1907/2006 (REACH), as amended]

DNEL Derived No-Effect Level.

EC10 A statistically calculated concentration of a chemical substance in an environmental medium that can cause

specific effects in 50% of the tested organisms of a given population under certain conditions.

EC50 (median effective concentration) - statistically calculated concentration of a chemical substance in an

environmental medium that can cause specific effects in 50% of the tested organisms of a given population

under certain conditions.

EN European standard

IATA The International Air Transport Association.
 IMDG International Maritime Dangerous Goods Code.
 ISO International Organization for Standardization

LC50 Concentration of a substance that is lethal to 50 percent of the organisms in a toxicity test.

LD50 Dose of a substance that is lethal to 50 percent of the organisms in a toxicity test.

NOEC The highest concentration that does not cause a statistically significant adverse effect in the exposed

population, when compared with its appropriate control.

OECD Organisation for Economic Cooperation and Development

PBT Persistent, bioaccumulative and toxic substance.

PNEC Predicted no-effect concentration.

RID The Regulation concerning the International Carriage of Dangerous Goods by Rail.

UFI Unique Formula Identifier

vPvB Very persistent and very bioaccumulative substance.

Acute Tox. 4 Acute toxicity - category 4

Aquatic Acute 1 Hazardous to the aquatic environment - Acute - category 1
Aquatic Chronic 1 Hazardous to the aquatic environment - Chronic - category 1
Aquatic Chronic 2 Hazardous to the aquatic environment - Chronic - category 2
Aquatic Chronic 3 Hazardous to the aquatic environment - Chronic - category 3

Asp. Tox. 1 Aspiration hazard - category 1

Eye Irrit. 2 Eye irritation - category 2

Flam. Liq. 3 Flammable liquid - category 3

Repr. 2 Reproductive toxicity - category 2

STOT SE 3 Specific target organ toxicity — single exposure - category 3

Skin Irrit. 2 Skin irritation - category 2
Skin Sens. 1 Skin sensitization - category 1
Skin Sens. 1A Skin sensitization - category 1A
Skin Sens. 1B Skin sensitization - category 1B

Trainings

Before commencing working with the product, the user should learn the Health & Safety regulations, regarding handling chemicals, and in particular, undergo a proper workplace training. Personnel related with the transport of hazardous substances in accordance with the ADR agreement should be trained and should obtain proper certification in a range of their obligations (general training, workplace training, safety training).

Key literature references and sources of data

This SDS was prepared on the basis of sheets of the individual components, literature data, online databases (eg. ECHA, TOXNET, COSING) as well as our knowledge and experience, taking into account current legislation.

Procedures used for the mixture classification according with Regulation 1272/2008/EC as amended

Flam. Liq. 3 H226 on basis of test data
Skin Irrit. 2 H315 calculation method
Skin Sens. 1 H317 calculation method
STOT SE 3 H336 calculation method
Aquatic Chronic 2 H411 calculation method



Date of issue: 31.08.2022
Date of update: —
Version: 1.0/EN

[Prepared in accordance with Regulation EC 1907/2006 (REACH), as amended]

Additional information

Changes: section: —

SDS issued by: THETA Consulting Sp. z o.o.

The information above is based on a current available data concerning the product, but also on the experience and knowledge in this field of the producer. They are neither a quality description of the product nor a guarantee of particular features. They are to be treated as aid to safety in transport, storage and usage of the product. That does not free the user from the responsibility of improper usage of the information above and also of improper compliance with the law norms in the field.